



Compressor pump K30 VG400 C 1.45L

K30



Product details

EAN	8712418346398
Manufacturer	Airpress Polska Sp. z o.o.
Weight (kg)	40 kg
SKU	K30
Motor power (hp / kW)	7.5 HP / 5.5 kW
Cylinder number	2
Number of stages	2
Intake capacity (l/min)	872 L/min (14.533 L/s)
Flywheel diameter (mm)	400 mm (4 dm)
Maximum pressure (bar)	11
Oilfree	No
Intercooler	Yes
After cooler	Yes
Compatible with	K 300-700 (36521-N), K 300-700S (36525-N), K 500-700S (36510-N), APZ 900+ (34650-S), APZ 600+ (34350-S)
Pump speed (rpm)	1200
Oil capacity (L)	1.45

Description

K30 piston compressor pump

K30 piston compressor pump is a reliable two-stage belt-driven pump, equipped with two pistons. Manufactured in the European Union, it meets the highest quality and safety standards, offering reliability and durability in the most demanding conditions.

The K30 model uses an advanced two-stage compression system that ensures exceptional performance and stability. Cast iron cylinders, forged crankshafts and wide ribs guarantee resistance to overload and long service life. Large pulleys with enlarged blades provide effective cooling, enabling intensive use without loss of performance.

Technical specifications:

Engine power: 7.5 HP (5.5 kW)

Performance: 872 l/min

Maximum pressure: 11 bar

Rotation speed: 1200 rpm

Number of pistons: 2

Number of compression stages: 2

Dimensions: 480 x 410 x 370 mm
Weight: 40 kg

The K30 pump is delivered without oil. Before starting work, top up with VG 100 specification oil to ensure optimal operation and safe use.



